

View Online at <https://aerobasegroup.com/nsn/5306-01-191-1414>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.541 inches

**Fastener Length:**

Between 0.917 inches and 0.946 inches

**Head Style:**

Spline extended washer

**Head Height:**

Between 0.302 inches and 0.322 inches

**Width Between Flats:**

Between 0.360 inches and 0.375 inches

**Extended Washer Diameter:**

Between 0.575 inches and 0.585 inches

**Extended Washer Thickness:**

Between 0.044 inches and 0.064 inches

**Hole Diameter:**

Between 0.050 inches and 0.060 inches

**Grip Diameter:**

Between 0.3110 inches and 0.3120 inches

**Thread Diameter:**

0.3125 inches

**Grip Length:**

Between 0.365 inches and 0.385 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c and 43.0 rockwell c

**Hole Configuration Style:**

Hexagon corners

**Material:**

Steel

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416 ty ii cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0