NSN 5306-01-191-1414

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-191-1414 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.541 inches **Fastener Length:** Between 0.917 inches and 0.946 inches **Head Style:** Spline extended washer **Head Height:** Between 0.302 inches and 0.322 inches Width Between Flats: Between 0.360 inches and 0.375 inches **Extended Washer Diameter:** Between 0.575 inches and 0.585 inches **Extended Washer Thickness:** Between 0.044 inches and 0.064 inches **Hole Diameter:** Between 0.050 inches and 0.060 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Thread Diameter:** 0.3125 inches **Grip Length:** Between 0.365 inches and 0.385 inches **Hole Quantity:** Hole Type: Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 180000 pounds per square inch **Hardness Rating:** 39.0 rockwell c and 43.0 rockwell c **Hole Configuration Style:** Hexagon corners Material:

Steel
Surface Treatment:
Cadmium

NSN 5306-01-191-1414

Shear Bolt - Page 2 of 2



Qq-p-416 ty ii cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A003b0