

View Online at <https://aerobasegroup.com/nsn/5306-01-191-2453>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.079 inches and 1.109 inches

**Fastener Length:**

Between 2.659 inches and 2.689 inches

**Head Style:**

Round w/wrench flats chamfered

**Head Diameter:**

1.380 inches

**Head Height:**

0.400 inches

**Width Between Flats:**

Between 1.053 inches and 1.066 inches

**Grip Diameter:**

Between 0.7445 inches and 0.74895 inches

**Shank Unthreaded Hole Diameter:**

0.144 inches first hole

**Thread Diameter:**

0.750 inches

**Grip Length:**

1.580 inches

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.375 inches first hole

**Surface Finish:**

16.0 microinches grip

**Material:**

Steel

**Material Specification:**

H+9-4-30 fscm 43999 mfr ref single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

La0109-019 fscm 43999 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0