

View Online at <https://aerobasegroup.com/nsn/5306-01-191-4586>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.125 inches

Fastener Length:

Between 0.708 inches and 0.728 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.309 inches and 0.329 inches

Width Between Flats:

Between 0.367 inches and 0.376 inches

Extended Washer Diameter:

Between 0.575 inches and 0.585 inches

Extended Washer Thickness:

Between 0.040 inches and 0.060 inches

Hole Diameter:

Between 0.050 inches and 0.060 inches

Grip Diameter:

Between 0.3110 inches and 0.3120 inches

Thread Diameter:

0.312 inches

Grip Length:

Between 0.583 inches and 0.603 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

200000 pounds per square inch

Hole Configuration Style:

Double hexagon longitudinal hole

Surface Finish:

32.0 microinches threads

Material:

Iron alloy 660

Material Specification:

Ams 5737 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0