

View Online at <https://aerobasegroup.com/nsn/5306-01-191-6278>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.843 inches and 0.893 inches

Fastener Length:

Between 3.978 inches and 4.008 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.608 inches and 0.628 inches

Width Between Flats:

Between 0.679 inches and 0.690 inches

Extended Washer Diameter:

Between 1.040 inches and 1.050 inches

Extended Washer Thickness:

0.150 inches

Grip Diameter:

Between 0.6230 inches and 0.6240 inches

Thread Diameter:

0.625 inches

Grip Length:

Between 3.115 inches and 3.135 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Material:

Steel comp h11

Material Specification:

Ams6485 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Mil-c-8837 type 2 cl 2 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.