NSN 5306-01-191-6279

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-191-6279

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.161 inches and 1.211 inches
Fastener Length:
Between 3.171 inches and 3.201 inches
Head Style:
Spline extended washer
Head Height:
Between 0.690 inches and 0.710 inches
Extended Washer Diameter:
Between 1.615 inches and 1.625 inches
Extended Washer Thickness:
Between 0.115 inches and 0.135 inches
Hole Diameter:
Between 0.050 inches and 0.060 inches
Grip Diameter:
Between 0.8730 inches and 0.8740 inches
Head Minor Diameter:
Between 0.923 inches and 0.938 inches
Thread Diameter:
0.875 inches
Grip Length:
Between 1.990 inches and 2.010 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
14
Min. Tensile Strength (psi):
220000 pounds per square inch
Hole Configuration Style:
Spline
Material:

Steel comp xm-13

Material Specification:

Ams5629 assn standard single material response

Surface Treatment:

Passivate

NSN 5306-01-191-6279

Shear Bolt - Page 2 of 2



Surface Treatment Spec	ific	ation:
------------------------	------	--------

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0