NSN 5306-01-191-6280

Shear Bolt - Page 1 of 2

Thread Class:

3a

View Online at https://aerobasegroup.com/nsn/5306-01-191-6280



Thread Direction: Right-hand Thread Length: Between 0.887 inches and 0.937 inches Fastener Length: Between 2.647 inches and 2.677 inches **Head Style:** Spline extended washer **Head Height:** Between 0.552 inches and 0.572 inches **Extended Washer Diameter:** Between 1.153 inches and 1.163 inches **Extended Washer Thickness:** Between 0.080 inches and 0.100 inches Hole Diameter: Between 0.045 inches and 0.065 inches **Grip Diameter:** Between 0.6230 inches and 0.6240 inches Head Minor Diameter: Between 0.673 inches and 0.688 inches **Thread Diameter:** 0.625 inches Grip Length: Between 1.740 inches and 1.760 inches **Hole Quantity:** 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 220000 pounds per square inch Hole Configuration Style: Spline Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response Surface Treatment: Passivate

NSN 5306-01-191-6280

Shear Bolt - Page 2 of 2



Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0