
NSN 5306-01-191-7482

Shear Bolt - Page 1 of 2





Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.742 inches and 0.792 inches Fastener Length: Between 2.314 inches and 2.344 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.494 inches and 0.514 inches Width Between Flats: Between 0.554 inches and 0.574 inches **Extended Washer Diameter:** Between 0.818 inches and 0.828 inches **Extended Washer Thickness:** Between 0.113 inches and 0.133 inches Hole Diameter: Between 0.050 inches and 0.060 inches **Grip Diameter:** Between 0.4990 inches and 0.4995 inches **Thread Diameter:** 0.500 inches Grip Length: Between 1.552 inches and 1.572 inches **Hole Quantity:** 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch Hole Configuration Style: Double hexagon longitudinal hole Material: Steel comp xm-13 Surface Treatment: Passivate **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response

NSN 5306-01-191-7482

Shear Bolt - Page 2 of 2

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

