

View Online at <https://aerobasegroup.com/nsn/5306-01-191-8243>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 1.000 inches and 1.188 inches

Fastener Length:

Between 1.710 inches and 1.750 inches

Head Style:

Hexagon

Head Height:

Between 0.226 inches and 0.243 inches

Width Between Flats:

Between 0.5510 inches and 0.5625 inches

Hole Diameter:

Between 0.060 inches and 0.068 inches

Locking Feature:

Patch threads or pellet threads or strip threads

Thread Diameter:

0.375 inches

Hole Quantity:

1

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

150000 pounds per square inch

Hardness Rating:

32.0 rockwell c fastener and 38.0 rockwell c fastener

Minimum Yield Strength:

120000 pounds per square inch

Hole Configuration Style:

Hexagon flats

Special Features:

Locking feature plastic polyamide

Material:

Steel

Material Specification:

Sae j429 grade 8 assn standard single material response fastener

Surface Treatment:

Zinc fastener and chromate fastener

Surface Treatment Specification:

Astm b633 type 2 sc 3 assn standard single treatment response fastener

Thread Series Designator:

Unf

Specification Or Standard:

10p style and 8 grade and 2 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A003b0