

View Online at <https://aerobasegroup.com/nsn/5306-01-192-0682>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.311 inches and 0.377 inches

**Fastener Length:**

Between 5.665 inches and 5.685 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.157 inches and 0.172 inches

**Width Between Flats:**

Between 0.492 inches and 0.502 inches

**Grip Diameter:**

Between 0.3108 inches and 0.3117 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole and 0.086 inches first hole

**Thread Diameter:**

0.312 inches

**Grip Length:**

Between 5.188 inches and 5.203 inches

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

36.0 rockwell c and 41.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

5.550 inches first hole and 5.580 inches first hole

**Surface Finish:**

63.0 microinches grip

**Special Features:**

Impedance locking element in shank

**Material:**

Steel comp e4340 fastener or steel comp 4140 fastener or steel comp 8740 fastener or steel comp 4130 fastener

**Material Specification:**

Ams5673 assn standard 1st material response spring or qq-w-423 cond b federal specification 2nd material response spring

**Surface Treatment:**

Passivate spring

**Surface Treatment Specification:**

Qq-p-416, ty2 cl2 federal specification single treatment response fastener

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0