

View Online at <https://aerobasegroup.com/nsn/5306-01-192-0682>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.311 inches and 0.377 inches

Fastener Length:

Between 5.665 inches and 5.685 inches

Head Style:

Dished hexagon

Head Height:

Between 0.157 inches and 0.172 inches

Width Between Flats:

Between 0.492 inches and 0.502 inches

Grip Diameter:

Between 0.3108 inches and 0.3117 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.086 inches first hole

Thread Diameter:

0.312 inches

Grip Length:

Between 5.188 inches and 5.203 inches

Thread Qty Per Inch (tpi):

24

Hardness Rating:

36.0 rockwell c and 41.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

5.550 inches first hole and 5.580 inches first hole

Surface Finish:

63.0 microinches grip

Special Features:

Impedance locking element in shank

Material:

Steel comp e4340 fastener or steel comp 4140 fastener or steel comp 8740 fastener or steel comp 4130 fastener

Material Specification:

Ams5673 assn standard 1st material response spring or qq-w-423 cond b federal specification 2nd material response spring

Surface Treatment:

Passivate spring

Surface Treatment Specification:

Qq-p-416, ty2 cl2 federal specification single treatment response fastener

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0