

View Online at <https://aerobasegroup.com/nsn/5306-01-192-3797>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.410 inches and 0.440 inches

Fastener Length:

Between 0.785 inches and 0.815 inches

Head Style:

Dished hexagon

Head Height:

Between 0.125 inches and 0.140 inches

Width Between Flats:

Between 0.429 inches and 0.439 inches

Locking Feature:

Patch threads

Grip Diameter:

Between 0.2485 inches and 0.2495 inches

Thread Diameter:

0.250 inches

Grip Length:

Between 0.365 inches and 0.385 inches

Thread Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Material:

Steel comp 4340 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416a, type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas6604 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.