
NSN 5306-01-193-4502

Shear Bolt - Page 1 of 2

3a

20

Unit Of Measure:





Thread Class: Thread Direction: Right-hand Thread Length: Between 0.440 inches and 0.507 inches Fastener Length: Between 1.512 inches and 1.559 inches **Head Style:** Double hexagon **Head Height:** Between 0.247 inches and 0.267 inches Width Between Flats: Between 0.678 inches and 0.689 inches **Grip Diameter:** Between 0.4358 inches and 0.4367 inches **Thread Diameter:** 0.438 inches Grip Length: Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 50.0 rockwell c **Product Name:** Navy special project Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response Surface Treatment: Cadmium or cadmium and chromate Surface Treatment Specification: Nas672 assn standard 1st treatment response or mil-c-8837 ty2 cl2 military specification 2nd treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

NSN 5306-01-193-4502

Shear Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.

