## NSN 5306-01-193-6830

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-193-6830

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.680 inches and 0.730 inches
Fastener Length:
Between 1.752 inches and 1.782 inches
Head Style:
Spline extended washer
Head Height:
Between 0.310 inches and 0.350 inches
Extended Washer Diameter:
Between 0.807 inches and 0.817 inches
Extended Washer Thickness:
Between 0.053 inches and 0.073 inches
Hole Diameter:
Between 0.050 inches and 0.060 inches
Grip Diameter:
Between 0.4365 inches and 0.4370 inches
Head Minor Diameter:
Between 0.514 inches and 0.521 inches
Thread Diameter:
0.437 inches
Grip Length:
Between 1.052 inches and 1.072 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
220000 pounds per square inch
Hole Configuration Style:
Spline
Material:

**Material Specification:** 

Steel comp xm-13

Ams5629 assn standard single material response

**Surface Treatment:** 

Passivate

## NSN 5306-01-193-6830

Shear Bolt - Page 2 of 2



Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0