## NSN 5306-01-193-6830

Shear Bolt - Page 1 of 2

**Thread Class:** 

View Online at https://aerobasegroup.com/nsn/5306-01-193-6830



## 3a **Thread Direction: Right-hand Thread Length:** Between 0.680 inches and 0.730 inches Fastener Length: Between 1.752 inches and 1.782 inches **Head Style:** Spline extended washer **Head Height:** Between 0.310 inches and 0.350 inches **Extended Washer Diameter:** Between 0.807 inches and 0.817 inches **Extended Washer Thickness:** Between 0.053 inches and 0.073 inches Hole Diameter: Between 0.050 inches and 0.060 inches Grip Diameter: Between 0.4365 inches and 0.4370 inches Head Minor Diameter: Between 0.514 inches and 0.521 inches **Thread Diameter:** 0.437 inches Grip Length: Between 1.052 inches and 1.072 inches **Hole Quantity:** 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch Hole Configuration Style: Spline Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response Surface Treatment: Passivate

## NSN 5306-01-193-6830

Shear Bolt - Page 2 of 2



Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

## Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0