## NSN 5306-01-193-7596

Shear Bolt - Page 1 of 2

**Thread Class:** 



View Online at https://aerobasegroup.com/nsn/5306-01-193-7596

3a
Thread Direction:
Right-hand
Thread Length:
Between 0.485 inches and 0.515 inches
Fastener Length:
Between 1.110 inches and 1.140 inches
Head Style:
Double hexagon w/hole
Head Height:
0.276 inches
Width Between Flats:
Between 0.367 inches and 0.376 inches
Extended Washer Diameter:
Between 0.521 inches and 0.531 inches
Extended Washer Thickness:
0.082 inches
Hole Diameter:
Between 0.050 inches and 0.060 inches
Grip Diameter:
Between 0.3115 inches and 0.3120 inches
Thread Diameter:
0.312 inches
Grip Length:
0.625 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Hole Configuration Style:
Double hexagon longitudinal hole
Material:

Ams 5629 assn standard single material response

Steel comp xm-13

**Material Specification:** 

## NSN 5306-01-193-7596

Shear Bolt - Page 2 of 2

A003b0



Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia: