## NSN 5306-01-193-9705

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-193-9705



**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

Between 0.443 inches and 0.493 inches

#### Fastener Length:

Between 1.578 inches and 1.608 inches

#### Head Style:

Spline extended washer

### Head Height:

Between 0.194 inches and 0.234 inches

### **Extended Washer Diameter:**

Between 0.460 inches and 0.470 inches

### **Extended Washer Thickness:**

Between 0.026 inches and 0.046 inches

#### **Grip Diameter:**

Between 0.2490 inches and 0.2495 inches

#### Head Minor Diameter:

Between 0.318 inches and 0.324 inches

## Thread Diameter:

0.250 inches

Grip Length:

Between 1.115 inches and 1.135 inches

### Thready Qty Per Inch (tpi):

28

### Min. Tensile Strength (psi):

220000 pounds per square inch

### Material:

Steel comp xm-13

### **Material Specification:**

Ams5629 assn standard single material response

#### Surface Treatment:

Passivate

## Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

## **Thread Series Designator:**

Unjf

Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5306-01-193-9705

Shear Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

