
# NSN 5306-01-194-4974

Machine Bolt - Page 1 of 2





# Thread Class:

2a

**Thread Direction:** 

Right-hand

### Thread Length:

Between 0.996 inches and 1.250 inches

#### Fastener Length:

Between 1.188 inches and 1.250 inches

#### Head Style:

Hexagon

Head Height:

Between 0.302 inches and 0.323 inches

#### Width Between Flats:

Between 0.736 inches and 0.750 inches

#### Locking Feature:

#### Patch threads or strip threads

**Thread Diameter:** 

0.500 inches

#### **Features Provided:**

Finished head

### Thready Qty Per Inch (tpi):

13

#### Min. Tensile Strength (psi):

150000 pounds per square inch

#### Hardness Rating:

32.0 rockwell c fastener and 38.0 rockwell c fastener

## **Special Features:**

Locking feature plastic polyamide

## Material:

Steel

# Material Specification:

Sae j429, grade 8 assn standard single material response fastener or astm a354, grade bd assn standard single material response fastener

## Surface Treatment:

Zinc fastener and chromate fastener

# Surface Treatment Specification:

Astm b633 type 2 sc 3 assn standard single treatment response fastener

# Thread Series Designator:

Unc

Shelf Life:

N/a

## Unit Of Measure:

---

# NSN 5306-01-194-4974

Machine Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

