## NSN 5306-01-194-4982

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-194-4982

| Thread Class:   |  |  |  |  |  |  |
|---|--|--|--|--|--|--|
| Inread Class:   |  |  |  |  |  |  |
| Thread Direction:                                       |  |  |  |  |  |  |
| Right-hand  |  |  |  |  |  |  |
| Thread Length:  |  |  |  |  |  |  |
| Between 0.526 inches and 0.576 inches                   |  |  |  |  |  |  |
| Fastener Length:  |  |  |  |  |  |  |
| Between 2.411 inches and 2.441 inches                   |  |  |  |  |  |  |
|   |  |  |  |  |  |  |
| Head Style:   |  |  |  |  |  |  |
| Spline extended washer                                  |  |  |  |  |  |  |
| Head Height:  |  |  |  |  |  |  |
| Between 0.302 inches and 0.322 inches                   |  |  |  |  |  |  |
| Extended Washer Diameter:                               |  |  |  |  |  |  |
| Between 0.575 inches and 0.585 inches                   |  |  |  |  |  |  |
| Extended Washer Thickness:                              |  |  |  |  |  |  |
| Between 0.035 inches and 0.055 inches                   |  |  |  |  |  |  |
| Grip Diameter:  |  |  |  |  |  |  |
| Between 0.3115 inches and 0.3120 inches                 |  |  |  |  |  |  |
| Head Minor Diameter:                                    |  |  |  |  |  |  |
| Between 0.383 inches and 0.389 inches                   |  |  |  |  |  |  |
| End Application:  |  |  |  |  |  |  |
| Aircraft, harrier av-8b                                 |  |  |  |  |  |  |
| Thread Diameter:  |  |  |  |  |  |  |
| 0.312 inches  |  |  |  |  |  |  |
| Grip Length:  |  |  |  |  |  |  |
| Between 1.865 inches and 1.885 inches                   |  |  |  |  |  |  |
| Thready Qty Per Inch (tpi):                             |  |  |  |  |  |  |
| 24  |  |  |  |  |  |  |
| Min. Tensile Strength (psi):                            |  |  |  |  |  |  |
| 220000 pounds per square inch                           |  |  |  |  |  |  |
| Material:   |  |  |  |  |  |  |
| Steel comp xm-13  |  |  |  |  |  |  |
| Material Specification:                                 |  |  |  |  |  |  |
| Ams 5629 assn standard single material response         |  |  |  |  |  |  |
| Surface Treatment:                                      |  |  |  |  |  |  |
| Passivate   |  |  |  |  |  |  |
| Surface Treatment Specification:                        |  |  |  |  |  |  |
| Qq-p-35 federal specification single treatment response |  |  |  |  |  |  |
| Thread Series Designator:                               |  |  |  |  |  |  |
| Unjf  |  |  |  |  |  |  |
| Shelf Life:   |  |  |  |  |  |  |
| N/a   |  |  |  |  |  |  |

## NSN 5306-01-194-4982

Shear Bolt - Page 2 of 2



|    | • • |             |     |     |      |
|----|-----|-------------|-----|-----|------|
| In | 18  | <i>(</i> )+ | МЛО | 201 | ure: |
|    |     |             |     |     |      |

--

Demilitarization:

No

Fiig:

A003b0