

View Online at <https://aerobasegroup.com/nsn/5306-01-194-8467>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.845 inches and 0.905 inches

Shank Length:

Between 0.845 inches and 0.905 inches

Eye Stock Diameter:

1.375 inches

Shoulder Diameter:

Between 0.743 inches and 0.748 inches

Shoulder Length:

Between 0.615 inches and 0.635 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole and 0.151 inches first hole

Ring Stock Diameter:

Between 0.417 inches and 0.457 inches

Thread Diameter:

0.562 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

160000 pounds per square inch

Distance From Threaded End To Shank Hole Center:

0.208 inches first hole and 0.228 inches first hole

Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150

Surface Treatment:

Cadmium and chromate or zinc and chromate

Surface Treatment Specification:

Qq-p-416, ty2 cl3 federal specification 1st treatment response or astm b633 assn standard 2nd treatment response

Style Designator:

Swivel

Thread Series Designator:

Unjf

Specification Data:

80205-nas1251 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0