
NSN 5306-01-194-9094

Shear Bolt - Page 1 of 2

Thread Class:

3a





Thread Direction: Right-hand Thread Length: Between 0.607 inches and 0.674 inches Fastener Length: Between 1.305 inches and 1.352 inches **Head Style:** Double hexagon **Head Height:** Between 0.271 inches and 0.291 inches Width Between Flats: Between 0.741 inches and 0.752 inches **Grip Diameter:** Between 0.4982 inches and 0.4991 inches Single Shear Strength: 132000 pounds per square inch **Thread Diameter:** 0.500 inches Grip Length: Between 0.678 inches and 0.698 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 50.0 rockwell c Surface Finish: 32.0 microinches grip **Product Name:** Navy special project Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium and chromate or cadmium **Surface Treatment Specification:** Mil-c-8837 type 2 cl 2 military specification 1st treatment response or nas 672 assn standard 2nd treatment response

Thread Series Designator:

Unjf

20

NSN 5306-01-194-9094

Shear Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.

