NSN 5306-01-194-9094

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-194-9094

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.607 inches and 0.674 inches
Fastener Length:
Between 1.305 inches and 1.352 inches
Head Style:
Double hexagon
Head Height:
Between 0.271 inches and 0.291 inches
Width Between Flats:
Between 0.741 inches and 0.752 inches
Grip Diameter:
Between 0.4982 inches and 0.4991 inches
Single Shear Strength:
132000 pounds per square inch
Thread Diameter:
0.500 inches
Grip Length:
Between 0.678 inches and 0.698 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Surface Finish:
32.0 microinches grip
Product Name:
Navy special project
Material:
Steel comp h11
Material Specification:
Ams 6487 assn standard single material response
Surface Treatment:
Cadmium and chromate or cadmium
Surface Treatment Specification:
Mil-c-8837 type 2 cl 2 military specification 1st treatment response or nas 672 assn standard 2nd treatment response
Thread Series Designator:

Unjf

NSN 5306-01-194-9094

Shear Bolt - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0

Mil-std (military Standard):

Mil-c-8837 spec.