NSN 5306-01-195-0047

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-195-0047

Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.568 inches and 0.618 inches	
Fastener Length:	
Between 2.703 inches and 2.733 inches	
Head Style:	
Double hexagon w/hole	
Head Height:	
Between 0.266 inches and 0.286 inches	
Width Between Flats:	
Between 0.367 inches and 0.376 inches	
Extended Washer Diameter:	
Between 0.521 inches and 0.531 inches	
Extended Washer Thickness:	
Between 0.072 inches and 0.092 inches	
Hole Diameter:	
Between 0.050 inches and 0.060 inches	
Grip Diameter:	
Between 0.3115 inches and 0.3120 inches	
Thread Diameter:	
0.312 inches	
Grip Length:	
Between 2.115 inches and 2.135 inches	
Hole Quantity:	
4	
Hole Type:	
Drilled	
Thready Qty Per Inch (tpi):	
24	
Min. Tensile Strength (psi):	
220000 pounds per square inch	
Hole Configuration Style:	
Double hexagon longitudinal hole	

Material:

Steel comp xm-13

Material Specification:

Ams5629 assn standard single material response

Surface Treatment:

Passivate

NSN 5306-01-195-0047

Shear Bolt - Page 2 of 2



Surface Treatment Spec	ific	ation:
------------------------	------	--------

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0