NSN 5306-01-195-0050

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-195-0050

view Offiline at https://aerobasegroup.com/hish/3300-01-133-0030
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.492 inches and 0.532 inches
Fastener Length:
Between 3.252 inches and 3.272 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.290 inches and 0.310 inches
Width Between Flats:
0.3125 inches
Extended Washer Diameter:
Between 0.428 inches and 0.438 inches
Extended Washer Thickness:
Between 0.059 inches and 0.079 inches
Hole Diameter:
Between 0.032 inches and 0.042 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 2.740 inches and 2.760 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
39.0 rockwell c and 43.0 rockwell c
Hole Configuration Style:
Double hexagon longitudinal hole
Material:
Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 6150
Surface Treatment:

Cadmium and chromate

NSN 5306-01-195-0050

Shear Bolt - Page 2 of 2



Surface	Treatment	Specification:
Juliace	HEAUHEIL	opecilication.

Qq-p-416, type 2 cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0