
## NSN 5306-01-195-1581

Machine Bolt - Page 1 of 2





## **Thread Class:** 2a **Thread Direction: Right-hand Thread Length:** 1.750 inches **Fastener Length:** Between 2.656 inches and 2.750 inches **Head Style:** Hexagon **Head Height:** Between 0.455 inches and 0.483 inches Width Between Flats: Between 1.100 inches and 1.125 inches Locking Feature: Patch threads or strip threads **Thread Diameter:** 0.750 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 10 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c fastener and 38.0 rockwell c fastener **Special Features:** Locking feature is plastic polyamide Material: Steel **Material Specification:** Sae j429, grade 8 assn standard single material response fastener or astm a354, grade bd assn standard single material response fastener Surface Treatment: Zinc fastener and chromate fastener Surface Treatment Specification: Astm b633 type 2 sc 3 assn standard single treatment response fastener **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure:

---

## NSN 5306-01-195-1581

Machine Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

