## NSN 5306-01-195-4998

Eye Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-195-4998

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.469 inches
Eye Inside Diameter:
Between 0.312 inches and 0.314 inches
Shoulder Thickness:
Between 0.068 inches and 0.088 inches
Shank Length:
Between 0.834 inches and 0.854 inches
Eye Stock Thickness:
Between 0.120 inches and 0.130 inches
Shoulder Diameter:
Between 0.490 inches and 0.510 inches
Shank Unthreaded Hole Diameter:
0.066 inches first hole and 0.086 inches first hole
Overall Length:
Between 1.583 inches and 1.603 inches
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi): 28
28
28 Min. Tensile Strength (psi):
28  Min. Tensile Strength (psi): 125000 pounds per square inch
28  Min. Tensile Strength (psi): 125000 pounds per square inch  Distance From Center Of Eye To Shank End:
28  Min. Tensile Strength (psi): 125000 pounds per square inch  Distance From Center Of Eye To Shank End: Between 1.302 inches and 1.322 inches
28  Min. Tensile Strength (psi): 125000 pounds per square inch  Distance From Center Of Eye To Shank End: Between 1.302 inches and 1.322 inches  Distance From Threaded End To Shank Hole Center:
Min. Tensile Strength (psi): 125000 pounds per square inch Distance From Center Of Eye To Shank End: Between 1.302 inches and 1.322 inches Distance From Threaded End To Shank Hole Center: 1.302 inches first hole and 1.322 inches first hole
Min. Tensile Strength (psi): 125000 pounds per square inch Distance From Center Of Eye To Shank End: Between 1.302 inches and 1.322 inches Distance From Threaded End To Shank Hole Center: 1.302 inches first hole and 1.322 inches first hole Eye Outside Width:
Min. Tensile Strength (psi): 125000 pounds per square inch Distance From Center Of Eye To Shank End: Between 1.302 inches and 1.322 inches Distance From Threaded End To Shank Hole Center: 1.302 inches first hole and 1.322 inches first hole Eye Outside Width: Between 0.490 inches and 0.510 inches
Min. Tensile Strength (psi): 125000 pounds per square inch Distance From Center Of Eye To Shank End: Between 1.302 inches and 1.322 inches Distance From Threaded End To Shank Hole Center: 1.302 inches first hole and 1.322 inches first hole Eye Outside Width: Between 0.490 inches and 0.510 inches Material:
Min. Tensile Strength (psi): 125000 pounds per square inch Distance From Center Of Eye To Shank End: Between 1.302 inches and 1.322 inches Distance From Threaded End To Shank Hole Center: 1.302 inches first hole and 1.322 inches first hole Eye Outside Width: Between 0.490 inches and 0.510 inches Material: Steel comp 302 or steel comp 304
Min. Tensile Strength (psi): 125000 pounds per square inch Distance From Center Of Eye To Shank End: Between 1.302 inches and 1.322 inches Distance From Threaded End To Shank Hole Center: 1.302 inches first hole and 1.322 inches first hole Eye Outside Width: Between 0.490 inches and 0.510 inches Material: Steel comp 302 or steel comp 304 Material Specification:
Min. Tensile Strength (psi): 125000 pounds per square inch Distance From Center Of Eye To Shank End: Between 1.302 inches and 1.322 inches Distance From Threaded End To Shank Hole Center: 1.302 inches first hole and 1.322 inches first hole Eye Outside Width: Between 0.490 inches and 0.510 inches Material: Steel comp 302 or steel comp 304 Material Specification: Qq-s-763 federal specification all material responses
Min. Tensile Strength (psi): 125000 pounds per square inch Distance From Center Of Eye To Shank End: Between 1.302 inches and 1.322 inches Distance From Threaded End To Shank Hole Center: 1.302 inches first hole and 1.322 inches first hole Eye Outside Width: Between 0.490 inches and 0.510 inches Material: Steel comp 302 or steel comp 304 Material Specification: Qq-s-763 federal specification all material responses Surface Treatment:
Min. Tensile Strength (psi): 125000 pounds per square inch Distance From Center Of Eye To Shank End: Between 1.302 inches and 1.322 inches Distance From Threaded End To Shank Hole Center: 1.302 inches first hole and 1.322 inches first hole Eye Outside Width: Between 0.490 inches and 0.510 inches Material: Steel comp 302 or steel comp 304 Material Specification: Qq-s-763 federal specification all material responses Surface Treatment: Passivate
Min. Tensile Strength (psi): 125000 pounds per square inch Distance From Center Of Eye To Shank End: Between 1.302 inches and 1.322 inches Distance From Threaded End To Shank Hole Center: 1.302 inches first hole and 1.322 inches first hole Eye Outside Width: Between 0.490 inches and 0.510 inches Material: Steel comp 302 or steel comp 304 Material Specification: Qq-s-763 federal specification all material responses Surface Treatment: Passivate Style Designator:

## NSN 5306-01-195-4998

Eye Bolt - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0