## NSN 5306-01-195-5019

Shear Bolt - Page 1 of 2

Between 0.380 inches and 0.390 inches

Between 0.630 inches and 0.650 inches

**Thread Class:** 

Right-hand

Thread Length:

**Thread Direction:** 

Fastener Length:

За



View Online at https://aerobasegroup.com/nsn/5306-01-195-5019

Head Style:				
Double hexagon w/hole				
Head Height:				
Between 0.204 inches and 0.224 inches				
Width Between Flats:				
Between 0.243 inches and 0.251 inches				
Extended Washer Diameter:				
Between 0.359 inches and 0.369 inches				
Extended Washer Thickness:				
Between 0.040 inches and 0.060 inches				
Grip Diameter:				
Between 0.1885 inches and 0.1895 inches				
Thread Diameter:				
0.190 inches				
Grip Length:				
0.250 inches				
Thready Qty Per Inch (tpi):				
32				
Min. Tensile Strength (psi):				
220000 pounds per square inch				
Hardness Rating:				
46.0 rockwell c and 50.0 rockwell c				
Surface Finish:				
32.0 microinches grip				
Material:				
Steel comp h11				
Material Specification:				
Ams 6487 assn standard single material response				
Surface Treatment:				
Nickel and cadmium and chromate				
Surface Treatment Specification:				
Ams 2416 assn standard all treatment responses				
Thread Series Designator:				
Unjf				

## NSN 5306-01-195-5019

Shear Bolt - Page 2 of 2



Spec	ifi	cation	Data
------	-----	--------	------

80205-nas1785 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0