NSN 5306-01-195-5022

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-195-5022

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.568 inches and 0.618 inches
Fastener Length:
Between 2.266 inches and 2.296 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.266 inches and 0.286 inches
Width Between Flats:
Between 0.367 inches and 0.376 inches
Extended Washer Diameter:
Between 0.521 inches and 0.531 inches
Extended Washer Thickness:
Between 0.072 inches and 0.092 inches
Hole Diameter:
Between 0.050 inches and 0.060 inches
Grip Diameter:
Between 0.3115 inches and 0.3120 inches
Thread Diameter:
0.312 inches
Grip Length:
Between 0.678 inches and 1.698 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Hole Configuration Style:
Double hexagon longitudinal hole
Double hexagon longitudinal hole

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

NSN 5306-01-195-5022

Shear Bolt - Page 2 of 2



Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0