

View Online at <https://aerobasegroup.com/nsn/5306-01-195-5055>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.013 inches and 1.100 inches

**Fastener Length:**

Between 5.335 inches and 5.402 inches

**Head Style:**

Spline drive shear head

**Head Height:**

0.468 inches

**Grip Diameter:**

Between 0.8735 inches and 0.8740 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole and 0.146 inches first hole

**Head Minor Diameter:**

1.298 inches

**Thread Diameter:**

0.875 inches

**Grip Length:**

Between 4.302 inches and 4.322 inches

**Thready Qty Per Inch (tpi):**

14

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

5.191 inches first hole and 5.268 inches first hole

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0