## NSN 5306-01-195-5813

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-195-5813

View Online at https://aerobasegroup.com/nsn/5306-01-195-5813				
Thread Class:				
3a				
Thread Direction:				
Right-hand				
Thread Length:				
Between 0.374 inches and 0.424 inches				
Fastener Length:				
Between 1.009 inches and 1.039 inches				
Head Style:				
Spline extended washer				
Head Height:				
Between 0.158 inches and 0.198 inches				
Extended Washer Diameter:				
Between 0.349 inches and 0.359 inches				
Extended Washer Thickness:				
Between 0.017 inches and 0.037 inches				
Grip Diameter:				
Between 0.1890 inches and 0.1895 inches				
Head Minor Diameter:				
Between 0.235 inches and 0.250 inches				
End Application:				
Harrier aircraft, av-8b				
Thread Diameter:				
0.190 inches				
Grip Length:				
Between 0.615 inches and 0.635 inches				
Thready Qty Per Inch (tpi):				
32				
Min. Tensile Strength (psi):				
220000 pounds per square inch				
Material:				
Steel comp xm-13				
Material Specification:				
Ams 5629 assn standard single material response				
Surface Treatment:				
Passivate or aluminum and chromate				
Surface Treatment Specification:				
Qq-p-35 federal specification 1st treatment response and mil-c-83488, type 2, cl 3 military specification 2nd treatment response				
Thread Series Designator:				
Unjf				
Shelf Life:				
N/a				

## NSN 5306-01-195-5813

Shear Bolt - Page 2 of 2



U	nit	Of	Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.