NSN 5306-01-195-7937

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-195-7937

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.589 inches and 0.639 inches |
| Fastener Length: |
| Between 1.849 inches and 1.879 inches |
| Head Style: |
| Spline extended washer |
| Head Height: |
| Between 0.263 inches and 0.303 inches |
| Extended Washer Diameter: |
| Between 0.691 inches and 0.701 inches |
| Extended Washer Thickness: |
| Between 0.044 inches and 0.064 inches |
| Hole Diameter: |
| Between 0.050 inches and 0.060 inches |
| Grip Diameter: |
| Between 0.3740 inches and 0.3745 inches |
| Head Minor Diameter: |
| Between 0.448 inches and 0.455 inches |
| Thread Diameter: |
| 0.375 inches |
| Grip Length: |
| Between 1.240 inches and 1.260 inches |
| Hole Quantity: |
| 4 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 24 |
| Min. Tensile Strength (psi): |
| 220000 pounds per square inch |
| Hole Configuration Style: |
| Spline |
| Product Name: |
| |

Material:

Steel comp xm-13

Navy special project

Material Specification:

Ams5629 assn standard single material response

NSN 5306-01-195-7937

Shear Bolt - Page 2 of 2

A003b0



| Surface Treatment: |
|---|
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |