

View Online at <https://aerobasegroup.com/nsn/5306-01-195-8360>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.340 inches

Fastener Length:

1.500 inches

Head Style:

Hexagon

Head Height:

0.180 inches

Width Between Flats:

Between 0.865 inches and 0.877 inches

Shoulder Diameter:

0.5605 inches first shoulder and 0.5615 inches first shoulder

Shoulder Length:

1.500 inches first shoulder

Thread Diameter:

0.312 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Shoulder Shape:

Round first shoulder

Material:

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416 type 1, cl 3 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.