
# NSN 5306-01-196-3856

Machine Bolt - Page 1 of 2





# Thread Class:

2a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

0.875 inches

#### Fastener Length:

Between 4.406 inches and 4.500 inches

#### Head Style:

Hexagon

Head Height:

Between 0.195 inches and 0.211 inches

#### Width Between Flats:

Between 0.489 inches and 0.500 inches

#### Locking Feature:

### Patch threads

Thread Diameter:

0.312 inches

#### **Features Provided:**

Finished head

# Thready Qty Per Inch (tpi):

18

### Min. Tensile Strength (psi):

150000 pounds per square inch

#### Hardness Rating:

32.0 rockwell c fastener and 38.0 rockwell c fastener

#### **Special Features:**

Locking feature material epoxy plastic

#### Material:

Steel

#### **Material Specification:**

Sae j429, grade 8 assn standard single material response fastener or astm a354, grade bd assn standard single material response fastener

#### Surface Treatment:

Zinc fastener and chromate fastener

#### Surface Treatment Specification:

Astm b633 type 2 sc 3 assn standard single treatment response fastener

#### **Thread Series Designator:**

Unc

# Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5306-01-196-3856

Machine Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

