## NSN 5306-01-196-8072

Shear Bolt - Page 1 of 2

Between 0.589 inches and 0.639 inches

Between 2.099 inches and 2.129 inches

**Thread Class:** 

Right-hand

Thread Length:

**Thread Direction:** 

Fastener Length:

Spline extended washer

**Head Style:** 

**Head Height:** 

За



View Online at https://aerobasegroup.com/nsn/5306-01-196-8072

Between 0.263 inches and 0.303 inches
Width Between Flats:
Between 0.448 inches and 0.455 inches
Extended Washer Diameter:
Between 0.691 inches and 0.701 inches
Extended Washer Thickness:
Between 0.044 inches and 0.064 inches
Hole Diameter:
Between 0.050 inches and 0.060 inches
Grip Diameter:
Between 0.3740 inches and 0.3745 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 1.490 inches and 1.510 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Hole Configuration Style:
Spline
Product Name:
Navy special project
Material Specification:
Ams5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf

## NSN 5306-01-196-8072

Shear Bolt - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0