NSN 5306-01-196-8073

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-196-8073

3a
Thread Direction:
Right-hand
Thread Length:
Between 0.499 inches and 0.549 inches
Fastener Length:
Between 1.384 inches and 1.414 inches
Head Style:
Spline extended washer
Head Height:
Between 0.302 inches and 0.322 inches
Extended Washer Diameter:
Between 0.349 inches and 0.359 inches
Extended Washer Thickness:
Between 0.017 inches and 0.037 inches
Hole Diameter:
Between 0.032 inches and 0.042 inches
Grip Diameter:
Between 0.1890 inches and 0.1895 inches
Head Minor Diameter:
Between 0.234 inches and 0.245 inches
Thread Diameter:
0.190 inches
Grip Length:
Between 0.865 inches and 0.885 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
Min. Tensile Strength (psi):
Min. Tensile Strength (psi): 220000 pounds per square inch
Min. Tensile Strength (psi): 220000 pounds per square inch Hole Configuration Style:

Surface Treatment: Passivate

Material Specification:

Ams5629 assn standard single material response

NSN 5306-01-196-8073

Shear Bolt - Page 2 of 2



Surface Treatment Speci

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0