## NSN 5306-01-197-2539

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-197-2539

Thread Class:  3a				
Thread Direction:				
Right-hand				
Thread Length:				
Between 0.568 inches and 0.618 inches				
Fastener Length:				
Between 2.078 inches and 2.108 inches				
Head Style:				
Double hexagon w/hole				
Head Height:				
Between 0.266 inches and 0.286 inches				
Width Between Flats:				
Between 0.367 inches and 0.376 inches				
Extended Washer Diameter:				
Between 0.521 inches and 0.531 inches				
Extended Washer Thickness:				
Between 0.072 inches and 0.092 inches				
Hole Diameter:				
Between 0.050 inches and 0.060 inches				
Grip Diameter:				
Between 0.3115 inches and 0.3120 inches				
Thread Diameter:				
0.312 inches				
Grip Length:				
Between 1.490 inches and 1.510 inches				
Hole Quantity:				
4				
Hole Type:				
Drilled				
Thready Qty Per Inch (tpi):				
24				
Min. Tensile Strength (psi):				
220000 pounds per square inch				
Hole Configuration Style:				
Double hexagon longitudinal hole				

Material:

Steel comp xm-13

**Material Specification:** 

Ams5629 assn standard single material response

**Surface Treatment:** 

Passivate

## NSN 5306-01-197-2539

Shear Bolt - Page 2 of 2



Surface	<b>Treatment</b>	Specifi	cation:
Juliace	I I Callillelli	Speciii	calion.

Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A003b0