

View Online at <https://aerobasegroup.com/nsn/5306-01-197-6592>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.614 inches

Fastener Length:

Between 3.162 inches and 3.192 inches

Head Style:

Spline extended washer

Head Height:

Between 0.327 inches and 0.347 inches

Extended Washer Diameter:

Between 0.691 inches and 0.701 inches

Extended Washer Thickness:

Between 0.044 inches and 0.064 inches

Hole Diameter:

Between 0.051 inches and 0.061 inches

Grip Diameter:

Between 0.3735 inches and 0.3745 inches

Head Minor Diameter:

Between 0.423 inches and 0.438 inches

Thread Diameter:

0.375 inches

Grip Length:

Between 2.552 inches and 2.572 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

220000 pounds per square inch

Hole Configuration Style:

Round longitudinal hole

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Aluminum and chromate

Surface Treatment Specification:

Mil-c-83488, type 2, class 2 military specification all treatment responses

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.