## NSN 5306-01-197-6592

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-197-6592

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.614 inches
Fastener Length:
Between 3.162 inches and 3.192 inches
Head Style:
Spline extended washer
Head Height:
Between 0.327 inches and 0.347 inches
Extended Washer Diameter:
Between 0.691 inches and 0.701 inches
Extended Washer Thickness:
Between 0.044 inches and 0.064 inches
Hole Diameter:
Between 0.051 inches and 0.061 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Head Minor Diameter:
Between 0.423 inches and 0.438 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 2.552 inches and 2.572 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Hole Configuration Style:
Round longitudinal hole
Material:
waterial.

Surface Treatment:

Steel comp xm-13

Aluminum and chromate

**Material Specification:** 

Ams 5629 assn standard single material response

## NSN 5306-01-197-6592

Shear Bolt - Page 2 of 2



Surface Treatment Spec	ific	ation:
------------------------	------	--------

Mil-c-83488, type 2, class 2 military specification all treatment responses

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.