# NSN 5306-01-198-3480

Shear Bolt - Page 1 of 2





### **Thread Class:**

3a

**Thread Direction:** 

Right-hand

## Thread Length:

Between 1.284 inches and 1.334 inches

## Fastener Length:

Between 4.419 inches and 4.449 inches

## Head Style:

Dished hexagon

## Head Height:

Between 0.500 inches and 0.515 inches

# Width Between Flats:

Between 1.427 inches and 1.440 inches

## Grip Diameter:

Between 0.9980 inches and 0.9990 inches

## Thread Diameter:

1.000 inches

# Grip Length:

Between 3.115 inches and 3.135 inches

## Thready Qty Per Inch (tpi):

12

## Min. Tensile Strength (psi):

160000 pounds per square inch

#### Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

# Surface Finish:

63.0 microinches grip

# Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150

# Surface Treatment:

Cadmium and chromate

# Surface Treatment Specification:

Qq-p-416, type 2 cl 2 federal specification single treatment response

# Thread Series Designator:

Unjf

### **Specification Data:**

80205-nas1316 professional/industrial association standard

# Shelf Life:

N/a

## Unit Of Measure:

--

# NSN 5306-01-198-3480

Shear Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

