## NSN 5306-01-198-5563

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-198-5563

**Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.320 inches and 0.370 inches **Fastener Length:** Between 0.518 inches and 0.548 inches **Head Style:** Dished hexagon **Head Height:** Between 0.110 inches and 0.125 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Grip Diameter:** Between 0.1890 inches and 0.1895 inches **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.178 inches and 0.198 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Surface Finish:** 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas6703 professional/industrial association standard Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5306-01-198-5563

Shear Bolt - Page 2 of 2



_					
11	em)	 tor	172	n	

No

Fiig:

A003b0