

View Online at <https://aerobasegroup.com/nsn/5306-01-198-6502>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.509 inches and 0.672 inches

Fastener Length:

Between 2.062 inches and 2.094 inches

Head Style:

Button

Head Diameter:

Between 1.484 inches and 1.516 inches

Head Height:

Between 0.422 inches and 0.453 inches

Groove Diameter:

Between 0.773 inches and 0.778 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole

Internal Drive Style:

Slot

End Application:

Spec item

Thread Diameter:

0.875 inches

Thready Qty Per Inch (tpi):

14

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

26.0 rockwell c and 32.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.876 inches first hole

Material:

Steel comp 8740 or steel comp 8735 or steel comp 4140 or steel comp 4130

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 ty2 cl2 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0