NSN 5306-01-198-8188

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-198-8188

View Online at https://aerobasegroup.com/nsn/5306-01-198-8188
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.945 inches and 0.995 inches
Fastener Length:
Between 2.455 inches and 2.485 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.608 inches and 0.628 inches
Width Between Flats:
Between 0.679 inches and 0.690 inches
Extended Washer Diameter:
Between 1.040 inches and 1.050 inches
Extended Washer Thickness:
Between 0.140 inches and 0.160 inches
Grip Diameter:
Between 0.6230 inches and 0.6240 inches
Thread Diameter:
0.625 inches
Grip Length:
Between 1.490 inches and 1.510 inches
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
200000 pounds per square inch
Surface Finish:
32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams 5737 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2 cl 2 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

N/a

NSN 5306-01-198-8188

Shear Bolt - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0