

View Online at <https://aerobasegroup.com/nsn/5306-01-199-3380>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.476 inches and 1.526 inches

Fastener Length:

Between 3.486 inches and 3.516 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.913 inches and 0.933 inches

Width Between Flats:

Between 1.054 inches and 1.074 inches

Extended Washer Diameter:

Between 1.615 inches and 1.625 inches

Extended Washer Thickness:

Between 0.202 inches and 0.232 inches

Grip Diameter:

Between 0.9990 inches and 0.9995 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole and 0.146 inches first hole

Thread Diameter:

1.000 inches

Grip Length:

Between 1.990 inches and 2.010 inches

Thready Qty Per Inch (tpi):

12

Min. Tensile Strength (psi):

220000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.097 inches first hole and 3.137 inches first hole

Material:

Steel comp xm-13

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0