NSN 5306-01-199-3412

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-199-3412

| Thread Class: 3a Thread Direction: Right-hand Thread Length: Between 0.568 inches and 0.618 inches Fastener Length: Between 2.328 inches and 2.358 inches Head Style: Double hexagon w/hole Head Height: Between 0.266 inches and 0.286 inches Width Between Flats: Between 0.367 inches and 0.376 inches Extended Washer Diameter: Between 0.521 inches and 0.531 inches Extended Washer Thickness: Between 0.072 inches and 0.092 inches Hole Diameter: Between 0.050 inches and 0.060 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Thread Diameter: 0.312 inches Grip Length: Between 1.740 inches and 1.760 inches Hole Quantity: 4 |
|---|
| Thread Direction: Right-hand Thread Length: Between 0.568 inches and 0.618 inches Fastener Length: Between 2.328 inches and 2.358 inches Head Style: Double hexagon w/hole Head Height: Between 0.266 inches and 0.286 inches Width Between Flats: Between 0.367 inches and 0.376 inches Extended Washer Diameter: Between 0.521 inches and 0.531 inches Extended Washer Thickness: Between 0.072 inches and 0.092 inches Hole Diameter: Between 0.050 inches and 0.060 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Thread Diameter: 0.312 inches Grip Length: Between 1.740 inches and 1.760 inches Hole Quantity: |
| Right-hand Thread Length: Between 0.568 inches and 0.618 inches Fastener Length: Between 2.328 inches and 2.358 inches Head Style: Double hexagon w/hole Head Height: Between 0.266 inches and 0.286 inches Width Between Flats: Between 0.367 inches and 0.376 inches Extended Washer Diameter: Between 0.521 inches and 0.531 inches Extended Washer Thickness: Between 0.072 inches and 0.092 inches Hole Diameter: Between 0.050 inches and 0.060 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Thread Diameter: 0.312 inches Grip Length: Between 1.740 inches and 1.760 inches Hole Quantity: |
| Thread Length: Between 0.568 inches and 0.618 inches Fastener Length: Between 2.328 inches and 2.358 inches Head Style: Double hexagon w/hole Head Height: Between 0.266 inches and 0.286 inches Width Between Flats: Between 0.367 inches and 0.376 inches Extended Washer Diameter: Between 0.521 inches and 0.531 inches Extended Washer Thickness: Between 0.072 inches and 0.092 inches Hole Diameter: Between 0.050 inches and 0.060 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Thread Diameter: 0.312 inches Grip Length: Between 1.740 inches and 1.760 inches Hole Quantity: |
| Between 0.568 inches and 0.618 inches Fastener Length: Between 2.328 inches and 2.358 inches Head Style: Double hexagon w/hole Head Height: Between 0.266 inches and 0.286 inches Width Between Flats: Between 0.367 inches and 0.376 inches Extended Washer Diameter: Between 0.521 inches and 0.531 inches Extended Washer Thickness: Between 0.072 inches and 0.092 inches Hole Diameter: Between 0.050 inches and 0.060 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Thread Diameter: 0.312 inches Grip Length: Between 1.740 inches and 1.760 inches Hole Quantity: |
| Fastener Length: Between 2.328 inches and 2.358 inches Head Style: Double hexagon w/hole Head Height: Between 0.266 inches and 0.286 inches Width Between Flats: Between 0.367 inches and 0.376 inches Extended Washer Diameter: Between 0.521 inches and 0.531 inches Extended Washer Thickness: Between 0.072 inches and 0.092 inches Hole Diameter: Between 0.050 inches and 0.060 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Thread Diameter: 0.312 inches Grip Length: Between 1.740 inches and 1.760 inches Hole Quantity: |
| Between 2.328 inches and 2.358 inches Head Style: Double hexagon w/hole Head Height: Between 0.266 inches and 0.286 inches Width Between Flats: Between 0.367 inches and 0.376 inches Extended Washer Diameter: Between 0.521 inches and 0.531 inches Extended Washer Thickness: Between 0.072 inches and 0.092 inches Hole Diameter: Between 0.050 inches and 0.060 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Thread Diameter: 0.312 inches Grip Length: Between 1.740 inches and 1.760 inches Hole Quantity: |
| Head Style: Double hexagon w/hole Head Height: Between 0.266 inches and 0.286 inches Width Between Flats: Between 0.367 inches and 0.376 inches Extended Washer Diameter: Between 0.521 inches and 0.531 inches Extended Washer Thickness: Between 0.072 inches and 0.092 inches Hole Diameter: Between 0.050 inches and 0.060 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Thread Diameter: 0.312 inches Grip Length: Between 1.740 inches and 1.760 inches Hole Quantity: |
| Double hexagon w/hole Head Height: Between 0.266 inches and 0.286 inches Width Between Flats: Between 0.367 inches and 0.376 inches Extended Washer Diameter: Between 0.521 inches and 0.531 inches Extended Washer Thickness: Between 0.072 inches and 0.092 inches Hole Diameter: Between 0.050 inches and 0.060 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Thread Diameter: 0.312 inches Grip Length: Between 1.740 inches and 1.760 inches Hole Quantity: |
| Head Height: Between 0.266 inches and 0.286 inches Width Between Flats: Between 0.367 inches and 0.376 inches Extended Washer Diameter: Between 0.521 inches and 0.531 inches Extended Washer Thickness: Between 0.072 inches and 0.092 inches Hole Diameter: Between 0.050 inches and 0.060 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Thread Diameter: 0.312 inches Grip Length: Between 1.740 inches and 1.760 inches Hole Quantity: |
| Between 0.266 inches and 0.286 inches Width Between Flats: Between 0.367 inches and 0.376 inches Extended Washer Diameter: Between 0.521 inches and 0.531 inches Extended Washer Thickness: Between 0.072 inches and 0.092 inches Hole Diameter: Between 0.050 inches and 0.060 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Thread Diameter: 0.312 inches Grip Length: Between 1.740 inches and 1.760 inches Hole Quantity: |
| Width Between Flats: Between 0.367 inches and 0.376 inches Extended Washer Diameter: Between 0.521 inches and 0.531 inches Extended Washer Thickness: Between 0.072 inches and 0.092 inches Hole Diameter: Between 0.050 inches and 0.060 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Thread Diameter: 0.312 inches Grip Length: Between 1.740 inches and 1.760 inches Hole Quantity: |
| Between 0.367 inches and 0.376 inches Extended Washer Diameter: Between 0.521 inches and 0.531 inches Extended Washer Thickness: Between 0.072 inches and 0.092 inches Hole Diameter: Between 0.050 inches and 0.060 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Thread Diameter: 0.312 inches Grip Length: Between 1.740 inches and 1.760 inches Hole Quantity: |
| Extended Washer Diameter: Between 0.521 inches and 0.531 inches Extended Washer Thickness: Between 0.072 inches and 0.092 inches Hole Diameter: Between 0.050 inches and 0.060 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Thread Diameter: 0.312 inches Grip Length: Between 1.740 inches and 1.760 inches Hole Quantity: |
| Between 0.521 inches and 0.531 inches Extended Washer Thickness: Between 0.072 inches and 0.092 inches Hole Diameter: Between 0.050 inches and 0.060 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Thread Diameter: 0.312 inches Grip Length: Between 1.740 inches and 1.760 inches Hole Quantity: |
| Extended Washer Thickness: Between 0.072 inches and 0.092 inches Hole Diameter: Between 0.050 inches and 0.060 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Thread Diameter: 0.312 inches Grip Length: Between 1.740 inches and 1.760 inches Hole Quantity: |
| Between 0.072 inches and 0.092 inches Hole Diameter: Between 0.050 inches and 0.060 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Thread Diameter: 0.312 inches Grip Length: Between 1.740 inches and 1.760 inches Hole Quantity: |
| Hole Diameter: Between 0.050 inches and 0.060 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Thread Diameter: 0.312 inches Grip Length: Between 1.740 inches and 1.760 inches Hole Quantity: |
| Between 0.050 inches and 0.060 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Thread Diameter: 0.312 inches Grip Length: Between 1.740 inches and 1.760 inches Hole Quantity: |
| Grip Diameter: Between 0.3115 inches and 0.3120 inches Thread Diameter: 0.312 inches Grip Length: Between 1.740 inches and 1.760 inches Hole Quantity: |
| Between 0.3115 inches and 0.3120 inches Thread Diameter: 0.312 inches Grip Length: Between 1.740 inches and 1.760 inches Hole Quantity: |
| Thread Diameter: 0.312 inches Grip Length: Between 1.740 inches and 1.760 inches Hole Quantity: |
| 0.312 inches Grip Length: Between 1.740 inches and 1.760 inches Hole Quantity: |
| Grip Length: Between 1.740 inches and 1.760 inches Hole Quantity: |
| Between 1.740 inches and 1.760 inches Hole Quantity: |
| Hole Quantity: |
| - |
| 4 |
| |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 24 |
| Min. Tensile Strength (psi): |
| 220000 pounds per square inch |
| Hole Configuration Style: |
| Double hexagon longitudinal hole |

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

NSN 5306-01-199-3412

Shear Bolt - Page 2 of 2



| Surface Treatment Spec | ific | ation: |
|------------------------|------|--------|
|------------------------|------|--------|

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0