NSN 5306-01-199-4351

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-199-4351

View Online at https://aerobasegroup.com/nsn/5306-01-199-4351
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.369 inches and 0.419 inches
Fastener Length:
Between 0.941 inches and 0.971 inches
Head Style:
Spline extended washer
Head Height:
Between 0.076 inches and 0.096 inches
Extended Washer Diameter:
Between 0.349 inches and 0.359 inches
Extended Washer Thickness:
Between 0.017 inches and 0.037 inches
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Head Minor Diameter:
Between 0.173 inches and 0.188 inches
Thread Diameter:
0.190 inches
Grip Length:
Between 0.552 inches and 0.572 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 43.0 rockwell c
Surface Finish:
32.0 microinches grip
Material:
Steel comp e4340 or steel comp 4140 or steel comp 6150 or steel comp 8740
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, ty2 cl2 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

NSN 5306-01-199-4351

Shear Bolt - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A003b0