

View Online at <https://aerobasegroup.com/nsn/5306-01-200-1430>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.410 inches and 0.500 inches

Fastener Length:

Between 0.610 inches and 0.640 inches

Head Style:

Double hexagon extended washer

Head Height:

Between 0.338 inches and 0.358 inches

Width Between Flats:

Between 0.367 inches and 0.376 inches

Extended Washer Diameter:

Between 0.521 inches and 0.531 inches

Extended Washer Thickness:

Between 0.072 inches and 0.092 inches

Hole Diameter:

Between 0.055 inches and 0.060 inches

Grip Diameter:

Between 0.2485 inches and 0.2495 inches

Thread Diameter:

0.312 inches

Grip Length:

Between 0.140 inches and 0.200 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

40.0 rockwell c and 43.0 rockwell c

Hole Configuration Style:

Double hexagon longitudinal hole

Surface Finish:

32.0 microinches threads

Special Features:

Finish color black

Material:

Steel comp h11 or steel comp e4340 or steel comp 8740

Surface Treatment:

Oxide

Surface Treatment Specification:

Mil-c-13924 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.