

View Online at <https://aerobasegroup.com/nsn/5306-01-201-0289>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

1.250 inches

**Fastener Length:**

Between 3.406 inches and 3.500 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.302 inches and 0.323 inches

**Width Between Flats:**

Between 0.736 inches and 0.750 inches

**Locking Feature:**

Patch threads or strip threads

**Thread Diameter:**

0.500 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

13

**Min. Tensile Strength (psi):**

120000 pounds per square inch

**Hardness Rating:**

25.0 rockwell c and 34.0 rockwell c

**Material:**

Steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1524 or steel comp 1025 or steel comp 1026 or steel comp 1527 or steel comp 1029 or steel comp 1030 or steel comp 1033 or steel comp 1034 or steel comp 1035 or steel comp 1536 or steel comp 1037 or steel comp 1038 or steel comp 1039 or steel comp 1040 or steel comp 1541

**Material Specification:**

Sae assn standard all material responses

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2 cl 3 federal specification single treatment response

**Thread Series Designator:**

Unc

**Specification Or Standard:**

2 type and 10p style and 5 grade

**Shelf Life:**

N/a

**Unit Of Measure:**

**Demilitarization:**

No

**Fig:**

A003b0