

View Online at <https://aerobasegroup.com/nsn/5306-01-201-9027>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.680 inches and 0.730 inches

Fastener Length:

Between 3.565 inches and 3.595 inches

Head Style:

Spline extended washer

Head Height:

0.330 inches

Width Between Flats:

Between 0.485 inches and 0.500 inches

Extended Washer Diameter:

Between 0.807 inches and 0.817 inches

Extended Washer Thickness:

Between 0.053 inches and 0.073 inches

Grip Diameter:

Between 0.4365 inches and 0.4370 inches

Shank Unthreaded Hole Diameter:

0.106 inches all holes and 0.116 inches all holes

Thread Diameter:

0.438 inches

Grip Length:

Between 2.865 inches and 2.885 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

220000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.341 inches all holes and 3.361 inches all holes

Special Features:

Two holes in shank at 90 degree angle to one another

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0