

View Online at <https://aerobasegroup.com/nsn/5306-01-202-0645>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.877 inches and 0.927 inches

Fastener Length:

Between 3.637 inches and 3.667 inches

Head Style:

Dished hexagon

Head Height:

Between 0.312 inches and 0.327 inches

Width Between Flats:

Between 0.928 inches and 0.940 inches

Grip Diameter:

Between 0.6230 inches and 0.6240 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole and 0.151 inches first hole

Thread Diameter:

0.625 inches

Grip Length:

Between 2.740 inches and 2.760 inches

Thread Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.378 inches first hole and 3.428 inches first hole

Surface Finish:

32.0 microinches threads

Material:

Steel comp e4340 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas6616 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.