NSN 5306-01-202-8969

Shear Bolt - Page 1 of 2

Thread Class:

Right-hand

Thread Direction:

Thread Length:

За



View Online at https://aerobasegroup.com/nsn/5306-01-202-8969

Between 0.618 inches and 0.668 inches **Fastener Length:** Between 1.878 inches and 1.908 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.378 inches and 0.398 inches Width Between Flats: Between 0.430 inches and 0.439 inches **Extended Washer Diameter:** Between 0.639 inches and 0.649 inches **Extended Washer Thickness:** Between 0.081 inches and 0.101 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches **Thread Diameter:** 0.375 inches **Grip Length:** Between 1.240 inches and 1.260 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 200000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 81205-bacb30le professional/industrial association standard

NSN 5306-01-202-8969

Shear Bolt - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0